



CEOS-ARD - Optical - Surface Temperature

Draft Version

This is a draft version. Please visit the [CEOS-ARD website](#) for the latest endorsed version of this document.

Document Status

Product Family Specification, Optical, Surface Temperature

Proposed revisions may be provided to: ard-contact@lists.ceos.org

Document History

2026-03-26 (PATCH)

- Renamed CARD4L to CEOS-ARD
- Restructured the document; removed empty or unused parts
- Split “Applies to” section into “Applies to” and “Background” sections
- Document history has been reset. Check the previous versions for details
- Numerical identifiers were rotated and are deprecated; new textual identifiers have been added
- The requirement “Radiometric corrections must lead to a valid measurement [...]” has been moved from the category description to the measurement requirement.
- If no threshold requirement applies, the wording has been made consistent (e.g. former req. 1.7 and 1.8).
- Former req. 1.9: Removed “on instrument” from “As threshold, but information on instrument should be available”.
- Former req. 2.3: Replaced the wording “e.g., due to missing ancillary data for some pixels.” with “This may be the result of missing ancillary data for a subset of the pixels.”

- Annex has been reformatted and updated

Justification: Migration to building blocks.

Editor: Matthias Mohr

Contributing Authors

- Adam Lewis, Geoscience Australia, Australia
- Jonathon Ross, Geoscience Australia, Australia
- Andreia Siqueira, Geoscience Australia, Australia
- Darcie Bontje, USGS, USA
- Steve Labahn, USGS, USA
- Mary Metzger, USGS, USA

CEOS Analysis Ready Data Definition

CEOS Analysis Ready Data (CEOS-ARD) are satellite data that have been processed to a minimum set of requirements and organized into a form that allows immediate analysis with a minimum of additional user effort and interoperability both through time and with other datasets.

Description

Product Family Specification: Optical, Surface Temperature (ST)

Version: 5.0.1-draft

Applies to: Data collected with multispectral sensors operating in the thermal infrared (TIR) wavelengths. These typically operate with ground sample distance and resolution in the order of 10-100m; however, the Specification is not inherently limited to this resolution.

Background

At present, surface temperature measurements tend to be provided as either surface brightness temperature (SBT) or as land surface temperatures (LST) requiring the SBT to be modified according to the emissivity of the target. This specification identifies the Surface Temperature (ST) as being the minimum or Threshold requirement for analysis ready land surface data. Nevertheless, both SBT and LST are land measurements, requiring atmospheric corrections.

Definitions and Abbreviations

Auxiliary Data

The data required for instrument processing, which does not originate in the instrument itself or from the satellite. Some auxiliary data will be generated in the ground segment, whilst other data will be provided from external sources, e.g., DEM, aerosols.

CEOS-ARD

Committee on Earth Observation Satellites - Analysis Ready Data

CEP

Circular Error Probability, often provided with an additional percentage (e.g. CEP90 for 90% probability)

DEM

Digital Elevation Model

DOI

Digital Object Identifier

GIS

Geographic Information System

LST

Land Surface Temperature

RMSE

Root Mean Square Error

rRMSE

Radial Root Mean Square Error

SBT

Surface Brightness Temperature

SI

International System of Units, internationally known by the abbreviation SI (from French *Système international d'unités*)

ST

Surface Temperature

TIR

Thermal Infrared

UTC

Coordinated Universal Time

WGS84

World Geodetic System 1984

Requirements

WARNING: The section numbers in front of the title (e.g. 1.1) are not stable and may change or may be removed at any time. Do **not** use the numbers to refer back to specific requirements! Instead, use the textual identifier that is provided below the title.

1. General Metadata

These are metadata records describing a distributed collection of pixels. The collection of pixels referred to must be contiguous in space and time. General metadata should allow the user to assess the *overall* suitability of the dataset, and must meet the requirements listed below.

1.1. Traceability

Identifier: meta-trace-st

Threshold requirements:

Not required.

Goal requirements:

Data must be traceable to SI reference standard. Information on traceability should be available in the metadata as a single DOI landing page.

- [Policy on measurement traceability](#)
- [Guidance on measurement traceability](#)

Note:

1. SI Traceability requires an estimate of measurement uncertainty.

.....

1.2. Metadata Machine Readability

Identifier: meta-memare-optical

Threshold requirements:

Metadata is provided in a structure that enables a computer algorithm to be used to consistently and automatically identify and extract each component part for further use.

Goal requirements:

As threshold, but metadata should be provided in a community endorsed standard that facilitates machine-readability, such as ISO 19115-2.

.....

1.3. Data Collection Time

Identifier: meta-time-st

Threshold requirements:

The start and stop time of data collection is identified in the metadata, expressed in date/time, to the second, with the time offset from UTC unambiguously identified.

Goal requirements:

Acquisition time for each pixel is identified (or can be reliably determined) in the metadata, expressed in date/time at UTC, to the second.

.....

1.4. Geographical Area

Identifier: meta-geoarea-st

Threshold requirements:

The surface location to which the data relates is identified, typically as a series of four corner points, expressed in an accepted coordinate reference system (e.g., WGS84 coordinates).

Goal requirements:

The geographic area covered by the observations is identified specifically, such as through a set of coordinates of a closely bounding polygon. The location to which each pixel refers is identified (or can be reliably determined) expressed in projection coordinates with reference datum.

.....

1.5. Coordinate Reference System

Identifier: meta-crs-optical

Threshold requirements:

The metadata lists the coordinate reference system that has been used.

Goal requirements:

As threshold.

.....

1.6. Map Projection

Identifier: meta-mapproj-st

Threshold requirements:

Not required.

Goal requirements:

The metadata lists the map projection that has been used, if any, and any relevant parameters required in relation to use of data in that map projection.

.....

1.7. Geometric Correction Methods

Identifier: meta-geocorm-st

Threshold requirements:

Not required.

Goal requirements:

Information on geometric correction methods should be available in the metadata as a single DOI landing page containing information on geodetic correction methods used, including reference database and auxiliary data such as elevation model(s) and reference chip-sets.

.....

1.8. Geometric Accuracy of the Data

Identifier: meta-geoacc-st

Threshold requirements:

Not required.

Goal requirements:

The metadata includes metrics describing the assessed geodetic accuracy of the data, expressed units of the coordinate system of the data. Accuracy is assessed by independent verification (as well as internal model-fit where applicable). Uncertainties are expressed as root mean square error (RMSE) or Circular Error 90% Probability (CEP90).

Note:

1. Information on geometric accuracy of the data should be available in the metadata as a single DOI landing page.
-

1.9. Instrument

Identifier: meta-instru-optical

Threshold requirements:

The instrument used to collect the data is identified in the metadata.

Goal requirements:

As threshold, but information should be available in the metadata as a single DOI landing page with references to the relevant CEOS Missions, Instruments, and Measurements Database record.

.....

1.10. Spectral Bands

Identifier: meta-specband

Threshold requirements:

The central wavelength for each band for which data is included is identified in the metadata, expressed in SI units.

Goal requirements:

As threshold, with instrument spectral response details (e.g., full spectral response function) also included or directly accessible using details in the metadata. Central wavelength and bandwidth at full-width half maximum value of the relative spectral response function are provided at least.

Note:

1. Information on spectral bands should be available in the metadata as a single DOI landing page.

.....

1.11. Sensor Calibration

Identifier: meta-sencal-optical

Threshold requirements:

Not required.

Goal requirements:

Sensor calibration parameters are identified in the metadata or can be accessed using details included in the metadata. Ideally this would support machine-to-machine access.

Note:

1. Information on sensory calibration should be available in the metadata as a single DOI landing page.

.....

1.12. Radiometric Accuracy

Identifier: meta-radacc-st

Threshold requirements:

Not required.

Goal requirements:

Information on radiometric accuracy should be available in the metadata as a single DOI landing page providing information on metrics describing the assessed absolute radiometric accuracy of the data, expressed as absolute radiometric uncertainty relative to a known reference standard.

Note:

1. For example, this may come from comparison with routine and rigorously collected in situ measurements.

.....

1.13. Algorithms

Identifier: meta-malgos-st

Threshold requirements:

All algorithms and versions, and the sequence in which they were applied in the generation process, are identified in the metadata.

Goal requirements:

As threshold, but only algorithms that have been published in a peer-reviewed journal.

Notes:

1. It is possible that high-quality corrections are applied through non-disclosed processes. CEOS-ARD does not per-se require full and open data and methods.
2. Information on algorithms should be available in the metadata as a single DOI landing page.

.....

1.14. Auxiliary Data

Identifier: meta-auxdat-optical

Threshold requirements:

The metadata identifies the sources of auxiliary data used in the generation process, ideally expressed as a single DOI landing page.

Note:

1. Auxiliary data includes DEMs, aerosols, etc. data sources.

Goal requirements:

As threshold, but information on auxiliary data should be available in the metadata as a single DOI landing page and is also available for free online download, contemporaneously with the product or through a link to the source.

[illegible]

1.15. Processing Chain Provenance

Identifier: meta-proprov-st

Threshold requirements:

Not required.

Goal requirements:

Information on processing chain provenance should be available in the metadata as a single DOI landing page containing description of the processing chain used to generate the product, including the versions of the software used and information on the data collection baseline, giving full transparency to the users.

[illegible]

1.16. Data Access

Identifier: meta-daccess

Threshold requirements:

Information on data access should be available in the metadata as a single DOI landing page.

Note:

1. Manual and offline interaction action (e.g., login) may be required.

Goal requirements:

As threshold.

.....

1.17. Overall Data Quality

Identifier: meta-odqual-st

Threshold requirements:

Not required.

Goal requirements:

The metadata includes details of the quality of the product based on quantitative assessment of the product with respect to high quality reference data with full traceability of the uncertainties. Validation and intercomparison statistics can provide the necessary quantification.

2. Per-Pixel Metadata

The following minimum metadata specifications apply to each pixel. Whether the metadata is provided in a single record relevant to all pixels, or separately for each pixel, is at the discretion of the data provider. Per-pixel metadata should allow users to **discriminate between** (choose) observations on the basis of their individual suitability for application.

2.1. Metadata Machine Readability

Identifier: pxl-pimemare

Threshold requirements:

Metadata is provided in a structure that enables a computer algorithm to be used to consistently and automatically identify and extract each component part for further use.

Goal requirements:

As threshold.

.....

2.2. No Data

Identifier: pxl-pinodat

Threshold requirements:

Pixels that do not correspond to an observation ('empty pixels') are flagged.

Goal requirements:

As threshold.

.....

2.3. Incomplete Testing

Identifier: pxl-pincot

Threshold requirements:

The metadata identifies pixels for which the per-pixel tests (below) have not all been successfully completed.

Note:

1. This may be the result of missing ancillary data for a subset of the pixels.

Goal requirements:

The metadata identifies which tests have, and have not, been successfully completed for each pixel.

.....

2.4. Saturation

Identifier: pxl-pisatur

Threshold requirements:

Metadata indicates where one or more pixel in the input spectral bands are saturated.

Goal requirements:

Metadata indicates which pixels are saturated for each spectral band.

.....

2.5. Cloud

Identifier: pxl-picloud

Threshold requirements:

Metadata indicates whether a pixel is assessed as being cloud.

Goal requirements:

As threshold, but information on cloud detection should be available in the metadata as a single DOI landing page.

.....

2.6. Cloud Shadow

Identifier: pxl-picloudsh

Threshold requirements:

Metadata indicates whether a pixel is assessed as being cloud shadow.

Goal requirements:

As threshold, but information on cloud shadow detection should be available in the metadata as a single DOI landing page.

.....

2.7. Snow/Ice Mask

Identifier: pxl-snowice-sr

Threshold requirements:

Not required.

Goal requirements:

The metadata indicates whether a pixel is assessed as being snow/ice or not. Information on snow/ice mask should be available in the metadata as a single DOI landing page.

.....

2.8. Solar and Viewing Geometry

Identifier: pxl-vigeso

Threshold requirements:

Provide average solar and sensor viewing azimuth and zenith angles.

Goal requirements:

Provide per-pixel solar and sensor viewing azimuth and zenith angles.

3. Radiometric and Atmospheric Corrections

The following requirements must be met for all pixels in a collection. The requirements indicate both the necessary outcomes and the minimum steps necessary to be deemed to have achieved those outcomes.

3.1. Measurand

Identifier: rac-measur-st

Threshold requirements:

Pixel values are a measurement of the Surface Temperature expressed in kelvin.

Note:

1. See 1.10

Goal requirements:

Surface temperature measurements are SI traceable (see also Section “[General Metadata: Traceability](#)”).

.....

3.2. Corrections for Atmosphere

Identifier: rac-catmos

Threshold requirements:

Retrieval methods for estimating surface temperature are provided.

Goal requirements:

As threshold.

.....

3.3. Adjustments for Emissivity and Anisotropy

Identifier: rac-emiani

Threshold requirements:

Retrieval methods for estimating surface emissivity per channel are provided.

Goal requirements:

As threshold, but the retrieval method for estimating the total directional emissivity is provided.

.....

3.4. Measurement Uncertainty

Identifier: rac-muncer-st

Threshold requirements:

A self-assessed declaration of per-pixel measurement uncertainty, following Section 3.2.4 (Uncertainty Characterization) of the Joint Earth Observation Mission Quality Assessment Framework - Optical Guidelines is provided, meeting the Basic or Good criteria.

Goal requirements:

A self-assessed declaration of per-pixel measurement uncertainty, following Section 3.2.4 (Uncertainty Characterization) of the Joint Earth Observation Mission Quality Assessment Framework - Optical Guidelines is provided, meeting the Excellent or Ideal criteria.

Note:

1. <https://science.nasa.gov/wp-content/uploads/2026/05/joint-optical-guidelines-jul2025-signed.pdf>

4. Geometric Corrections

The geometric corrections are steps that are taken to place the measurement accurately on the surface of the Earth (that is, to geolocate the measurement) allowing measurements taken through time to be compared. This section specifies any geometric correction requirements that must be met in order for the data to be analysis ready.

4.1. Geometric Correction

Identifier: gcor-geocorr-st

Threshold requirements:

Sub-pixel accuracy is achieved in **relative** geolocation, that is, the pixels from the same instrument and platform are consistently located, and are thus comparable, through time.

Sub-pixel accuracy is taken to be less than or equal to 0.5 pixel radial root mean square error (rRMSE) or equivalent in Circular Error Probability (CEP) relative to a defined reference image.

A consistent gridding/sampling frame is necessary to meet this requirement.

Relevant metadata must be provided under Section “[General Metadata: Geometric Accuracy of the Data](#)” and Section “[General Metadata: Instrument](#)”.

Note:

1. The threshold level will not necessarily enable interoperability between data from **different** sources as the geometric corrections for each of the sources may differ.

Goal requirements:

Sub-pixel accuracy is achieved relative to an identified absolute independent terrestrial referencing system (such as a national map grid).

A consistent gridding/sampling frame is necessary to meet this requirement.

Relevant metadata must be provided under Section "[General Metadata: Geometric Accuracy of the Data](#)" and Section "[General Metadata: Instrument](#)".

Note:

1. This requirement is intended to enable interoperability between imagery from different platforms that meet this level of correction, and with non-image spatial data such as GIS layers and terrain models.

Introduction

This section aims to provide background and specific information on the processing steps that can be used to achieve analysis ready data for a specific and well-developed Product Family Specification. This Guidance material does not replace or override the specifications.

What is CEOS Analysis Ready Data?

CEOS-ARD are products that have been processed to a minimum set of requirements and organized into a form that allows immediate analysis with a minimum of additional user effort. In general, these products would be resampled onto a common geometric grid (for a given product) and would provide baseline data for further interoperability both through time and with other datasets.

CEOS-ARD products are intended to be flexible and accessible products suitable for a wide range of users for a wide variety of applications, including particularly time series analysis and multi-sensor application development. They are also intended to support rapid ingestion and exploitation via high-performance computing, cloud computing and other future data architectures. They may not be suitable for all purposes and are not intended as a *replacement* for other types of satellite products.

When can a product be called CEOS-ARD?

The CEOS-ARD branding is applied to a particular product once:

- that product has been assessed as meeting CEOS-ARD requirements by the agency responsible for production and distribution of the product, and
- that the assessment has been peer reviewed by the relevant CEOS team(s).

Agencies or other entities considering undertaking an assessment process should consult the [CEOS-ARD Governance Framework](#).

A product can continue to use CEOS-ARD branding as long as its generation and distribution remain consistent with the peer-reviewed assessment.

What is the difference between Threshold and Goal?

Threshold (Minimum) requirements are the **minimum** that is needed for the data to be analysis ready. This must be practical and accepted by the data producers.

Goal (Desired) requirements (previously referred to as “Target”) are the ideal; where we would like to be. Some providers may already meet these.

Products that meet all *threshold* requirements should be immediately useful for scientific analysis or decision-making.

Products that meet *goal* requirements will reduce the overall product uncertainties and enhance broad-scale applications. For example, the products may enhance interoperability or provide increased accuracy through additional corrections that are not reasonable at the *threshold* level.

Goal requirements anticipate continuous improvement of methods and evolution of community expectations, which are both normal and inevitable in a developing field. Over time, *goal* specifications may (and subject to due process) become accepted as *threshold* requirements.

References

- Cook, Monica, John R. Schott, John Mandel, and Nina Raqueno. 2014. "Development of an Operational Calibration Methodology for the Landsat Thermal Data Archive and Initial Testing of the Atmospheric Compensation Component of a Land Surface Temperature (LST) Product from the Archive." *Remote Sensing* 6 (11): 11244–66. <https://doi.org/10.3390/rs6111244>.
- International Organization for Standardization. 2009. *Geographic information — Metadata — Part 2: Extensions for imagery and gridded data*. Standard. International Organization for Standardization.
- Li, Zhao-Liang, Bo-Hui Tang, Hua Wu, et al. 2013. "Satellite-Derived Land Surface Temperature: Current Status and Perspectives." *Remote Sensing of Environment* 131: 14–37. <https://doi.org/https://doi.org/10.1016/j.rse.2012.12.008>.

Annexes

CEOS-ARD Requirement Examples (Surface Temperature)

General Metadata

Traceability

Refers to Section "[General Metadata: Traceability](#)"

Example of measurement traceability in metadata:

```
<band add_offset="0.000000" category="image" data_type="INT16"
      fill_value="-9999" name="ST" nlines="5000" nsamps="5000"
      product="st" scale_factor="0.100000">
  <short_name>LC08ST</short_name>
  <long_name>Surface Temperature</long_name>
  <file_name>ST</file_name>
  <pixel_size units="meters" x="30" y="30"/>
  <resample_method>none</resample_method>
  <data_units>temperature (kelvin)</data_units>
  <valid_range max="3730.000000" min="1500.000000"/>
  <app_version>st_1.3.0</app_version>
  <production_date>2018-11-30T04:47:38Z</production_date>
</band>
```

Example of measurement uncertainty in metadata:

```
<band category="qa" data_type="INT16" fill_value="-9999" name="STQA"
      nlines="5000" nsamps="5000" product="st_qa"
      scale_factor="0.010000" source="toa_refl">
  <short_name>LC08STQA</short_name>
  <long_name>Surface temperature quality band</long_name>
  <file_name>STQA</file_name>
  <pixel_size units="meters" x="30" y="30"/>
  <resample_method>none</resample_method>
  <data_units>temperature (kelvin)</data_units>
  <valid_range max="32767.000000" min="0.000000"/>
  <app_version>st_1.3.0</app_version>
  <production_date>2018-11-30T04:47:38Z</production_date>
</band>
```

Data Collection Time

Refers to Section "[General Metadata: Data Collection Time](#)"

Example of scene center time (UTC):

```
<scene_center_time>17:23:57.201686Z</scene_center_time>
```

The granule start and end times are contained in the XML metadata:

```
<metadataObject ID="acquisitionPeriod" classification="DESCRIPTION"
  category="DMD">
  <metadataWrap mimeType="text/xml" vocabularyName="Sentinel-SAFE"
    textInfo="Acquisition Period">
    <xmlData>
      <sentinel-safe:acquisitionPeriod>
        <sentinel-safe:startTime>2018-10-
          07T05:04:50.425838Z</sentinel-safe:startTime>
        <sentinel-safe:stopTime>2018-10-
          07T05:07:50.425838Z</sentinel-safe:stopTime>
      </sentinel-safe:acquisitionPeriod>
    </xmlData>
  </metadataWrap>
</metadataObject>
```

Per pixel times are derived using information from the “time_in.nc” and “indices_in.nc” datafiles following a prescribed recipe.

Geographical Area

Refers to Section [“General Metadata: Geographical Area”](#)

Example of the bounding coordinates in decimal degrees (WGS84):

```
<bounding_coordinates>
  <west>-99.9109607425</west>
  <east>-98.0134952569</east>
  <north>43.3609828699</north>
  <south>41.9778528562</south>
</bounding_coordinates>
```

Example of the corner points in the map projection system (Albers):

```
<corner_point location="UL" x="-315585.000000" y="2264805.000000"/>
<corner_point location="LR" x="-165585.000000" y="2114805.000000"/>
```

Map Projection

Refers to Section [“General Metadata: Map Projection”](#)

```
<projection_information datum="WGS84" projection="AEA" units="meters">
  <corner_point location="UL" x="-315585.000000" y="2264805.000000"/>
  <corner_point location="LR" x="-165585.000000" y="2114805.000000"/>
  <grid_origin>UL</grid_origin>
  <albers_proj_params>
    <standard_parallel1>29.500000</standard_parallel1>
    <standard_parallel2>45.500000</standard_parallel2>
```

```

    <central_meridian>-96.000000</central_meridian>
    <origin_latitude>23.000000</origin_latitude>
    <false_easting>0.000000</false_easting>
    <false_northing>0.000000</false_northing>
  </albers_proj_params>
</projection_information>

```

Geometric Correction Source

Refers to Section “[General Metadata: Geometric Correction Methods](#)”

Example of elevation source:

```
<elevation_source>GLS2000</elevation_source>
```

The XML wrapper provides the source of the geometric calibration:

```

<sentinel-safe:resource
  name="S3A_SL_1_GEC_AX_20160216T000000_20991231T235959_20180202T12
  0000_MPC_O_AL_007.SEN3" role="SLSTR Geometric
  Calibration Data File">
  <sentinel-safe:processing name="AdfProcessing">
    <sentinel-safe:facility name="ESA Mission Performance Coordinating
    Centre (MPC)" organisation="ESA Mission Performance Coordinating
    Centre" site="Sophia Antipolis" country="France">
      <sentinel-safe:hardware name="OPE"/>
      <sentinel-safe:software name="ADC" version="1.0"/>
    </sentinel-safe:facility>
  </sentinel-safe:processing>
</sentinel-safe:resource>

```

Geometric Accuracy of the Data

Refers to Section “[General Metadata: Geometric Accuracy of the Data](#)”

```

<geometric_rmse_model>9.021</geometric_rmse_model>
<geometric_rmse_model_x>6.864</geometric_rmse_model_x>
<geometric_rmse_model_y>5.854</geometric_rmse_model_y>

```

Instrument

Refers to Section “[General Metadata: Instrument](#)”

```

<satellite>LANDSAT_8</satellite>
<instrument>OLI/TIRS_Combined</instrument>

```

The XML wrapper provides the instrument details:

```

<metadataObject ID="platform" classification="DESCRIPTION"
  category="DMD">
  <metadataWrap mimeType="text/xml" vocabularyName="Sentinel-SAFE"
    textInfo="Platform Description">

```

```

<xmlData>
  <sentinel-safe:platform>
    <sentinel-safe:nssdcIdentifier>2016-011A</sentinel-
safe:nssdcIdentifier>
    <sentinel-safe:familyName>Sentinel-3</sentinel-
safe:familyName>
    <sentinel-safe:number>A</sentinel-safe:number>
    <sentinel-safe:instrument>
      <sentinel-safe:familyName abbreviation="SLSTR">Sea and
Land Surface Temperature Radiometer</sentinel-safe:familyName>
      <sentinel-safe:mode identifier="E0">Earth
Observation</sentinel-safe:mode>
    </sentinel-safe:instrument>
  </sentinel-safe:platform>
</xmlData>
</metadataWrap>
</metadataObject>

```

Sensor Calibration

Refers to Section [“General Metadata: Sensor Calibration”](#)

```
<cpf_name>LC08CPF_20180101_20180331_01.02</cpf_name>
```

Algorithms

Refers to Section [“General Metadata: Algorithms”](#)

Example for Surface Temperature algorithm version:

```
<app_version>st_1.3.0</app_version>
```

Auxiliary Data

Refers to Section [“General Metadata: Auxiliary Data”](#)

All Auxiliary Datafiles (ADFs) are listed in the XML wrapper:

```

<sentinel-safe:resource
  name="S3__SL_2_LSTBAX_20000101T000000_20991231T235959_20151214T12
0000_____MPC_0_AL_001.SEN3" role="SLSTR LST biome
data file" version="06.16">
<sentinel-safe:resource
  name="S3__SL_2_LSTVAX_20000101T000000_20991231T235959_20151214T12
0000_____MPC_0_AL_001.SEN3" role="SLSTR LST
vegetation fraction data file" version="06.16">
<sentinel-safe:resource
  name="S3__SL_2_LSTWAX_20000101T000000_20991231T235959_20151214T12
0000_____MPC_0_AL_001.SEN3" role="SLSTR LST water
vapour data file" version="06.16">

```

Processing Chain Provenance

Refers to Section [“General Metadata: Processing Chain Provenance”](#)

Processing chain provenance information is stored in the XML wrapper under the following tag:

```
<metadataObject ID="processing" classification="PROVENANCE"
  category="PDI">
```

Overall Data Quality

Refers to Section [“General Metadata: Overall Data Quality”](#)

Overall data quality information is stored in the XML wrapper under the following tag:

```
<metadataObject ID="measurementQualityInformation"
  classification="DESCRIPTION" category="DMD">
```

Per-Pixel Metadata

No Data

Refers to Section [“Per-Pixel Metadata: No Data”](#)

Example of the fill_value specified for each band in metadata:

```
<band add_offset="0.000000" category="image" data_type="INT16"
  fill_value="-9999" name="ST" nlines="5000" nsamps="5000"
  product="st" scale_factor="0.100000">
  <short_name>LC08ST</short_name>
  <long_name>Surface Temperature</long_name>
  <file_name>ST</file_name>
  <pixel_size units="meters" x="30" y="30"/>
  <resample_method>none</resample_method>
  <data_units>temperature (kelvin)</data_units>
  <valid_range max="3730.000000" min="1500.000000"/>
  <app_version>st_1.3.0</app_version>
  <production_date>2018-11-30T04:47:38Z</production_date>
</band>
```

The “flags_in.nc” datafile contains per-pixel information on “no / bad data through saturation / incomplete testing etc”. The following field has an “unfilled” flag:

```
ushort confidence_in(rows, columns) ;
  confidence_in:flag_masks = 1US, 2US, 4US, 8US, 16US, 32US, 64US, 128US,
  256US, 512US, 1024US, 2048US, 4096US, 8192US, 16384US, 32768US ;
  confidence_in:flag_meanings = "coastline ocean tidal land inland_water
  unfilled spare spare cosmetic duplicate day twilight sun_glint snow
  summary_cloud summary_pointing" ;
```

Incomplete Testing

Refers to Section [“Per-Pixel Metadata: Incomplete Testing”](#)

The “flags_in.nc” datafile contains per-pixel information on “no / bad data through saturation / incomplete testing etc”. The following field has an “unfilled” flag:

```
ushort confidence_in(rows, columns) ;
    confidence_in:flag_masks = 1US, 2US, 4US, 8US, 16US, 32US, 64US, 128US,
256US, 512US, 1024US, 2048US, 4096US, 8192US, 16384US, 32768US ;
    confidence_in:flag_meanings = "coastline ocean tidal land inland_water
unfilled spare spare cosmetic duplicate day twilight sun_glint snow
summary_cloud summary_pointing";
```

Saturation

Refers to Section [“Per-Pixel Metadata: Saturation”](#)

Example of RADSATQA band showing the saturation information for the thermal bands used for Surface Temperature calculation:

```
<band category="qa" data_type="UINT16" fill_value="1" name="RADSATQA"
    nlines="5000" nsamps="5000" product="toa_refl" source="level1">
    <short_name>LC08RADSAT</short_name>
    <long_name>saturation mask</long_name>
    <file_name>RADSATQA</file_name>
    <pixel_size units="meters" x="30" y="30"/>
    <resample_method>none</resample_method>
    <data_units>bitmap</data_units>
    <bitmap_description>
        <bit num="0">Data Fill Flag (0 = valid data, 1 = invalid data)
        </bit>
        <bit num="1">Band 1 Data Saturation Flag (0 = valid data, 1 =
        saturated data)</bit>
        <bit num="2">Band 2 Data Saturation Flag (0 = valid data, 1 =
        saturated data)</bit>
        <bit num="3">Band 3 Data Saturation Flag (0 = valid data, 1 =
        saturated data)</bit>
        <bit num="4">Band 4 Data Saturation Flag (0 = valid data, 1 =
        saturated data)</bit>
        <bit num="5">Band 5 Data Saturation Flag (0 = valid data, 1 =
        saturated data)</bit>
        <bit num="6">Band 6 Data Saturation Flag (0 = valid data, 1 =
        saturated data)</bit>
        <bit num="7">Band 7 Data Saturation Flag (0 = valid data, 1 =
        saturated data)</bit>
        <bit num="8">N/A</bit>
        <bit num="9">Band 9 Data Saturation Flag (0 = valid data, 1 =
        saturated data)</bit>
        <bit num="10">Band 10 Data Saturation Flag (0 = valid data, 1 =
        saturated data)</bit>
        <bit num="11">Band 11 Data Saturation Flag (0 = valid data, 1 =
        saturated data)</bit>
    </bitmap_description>
```

```

    <app_version>LaSRC_1.3.0</app_version>
    <production_date>2018-11-30T04:47:38Z</production_date>
  </band>

```

The “flags_in.nc” datafile contains per-pixel information on “no / bad data through saturation / incomplete testing etc”. The following field has an “unfilled” flag:

```

ushort confidence_in(rows, columns) ;
    confidence_in:flag_masks = 1US, 2US, 4US, 8US, 16US, 32US, 64US, 128US,
    256US, 512US, 1024US, 2048US, 4096US, 8192US, 16384US, 32768US ;
    confidence_in:flag_meanings = "coastline ocean tidal land inland_water
unfilled spare spare cosmetic duplicate day twilight sun_glint snow
summary_cloud summary_pointing" ;

```

Cloud

Refers to Section [“Per-Pixel Metadata: Cloud”](#)

Example of PIXELQA showing the bit value for cloud pixels (as well as cloud and cirrus confidence):

```

<band category="qa" data_type="UINT16" fill_value="1" name="PIXELQA"
    nlines="5000" nsamps="5000" product="level2_qa" source="level1">
  <short_name>LC08PQA</short_name>
  <long_name>level-2 pixel quality band</long_name>
  <file_name>PIXELQA</file_name>
  <pixel_size units="meters" x="30" y="30"/>
  <resample_method>none</resample_method>
  <data_units>quality/feature classification</data_units>
  <bitmap_description>
    <bit num="0">fill</bit>
    <bit num="1">clear</bit>
    <bit num="2">water</bit>
    <bit num="3">cloud shadow</bit>
    <bit num="4">snow</bit>
    <bit num="5">cloud</bit>
    <bit num="6">cloud confidence</bit>
    <bit num="7">cloud confidence</bit>
    <bit num="8">cirrus confidence</bit>
    <bit num="9">cirrus confidence</bit>
    <bit num="10">terrain occlusion</bit>
    <bit num="11">unused</bit>
    <bit num="12">unused</bit>
    <bit num="13">unused</bit>
    <bit num="14">unused</bit>
    <bit num="15">unused</bit>
  </bitmap_description>
  <app_version>generate_pixel_qa_1.6.0</app_version>
  <production_date>2018-11-30T04:47:38Z</production_date>
</band>

```

The “flags_in.nc” datafile contains all the cloud masking flags. Three fields are relevant:

1. cloud_in
2. confidence_in
3. bayes_in

The “cloud_in” field contains all the individual threshold-based mask:

```
flag_masks = 1US, 2US, 4US, 8US, 16US, 32US, 64US, 128US, 256US, 512US,
            1024US, 2048US, 4096US, 8192US, 16384US, 32768US ;
cloud_in:flag_meanings = "visible 1.37_threshold 1.6_small_histogram
                        1.6_large_histogram 2.25_small_histogram 2.25_large_histogram
                        11_spatial_coherence gross_cloud thin_cirrus medium_high
                        fog_low_stratus 11_12_view_difference 3.7_11_view_difference
                        thermal_histogram spare spare"
```

The “confidence_in” field contains the “summary_cloud_mask” from the most appropriate cloud_in flags; the value of the bit is 16384US. The “bayes_in” field contains the “single_moderate” probabilistic cloud flag; the value of the bit is 2UB.

Cloud Shadow

Refers to Section “[Per-Pixel Metadata: Cloud Shadow](#)”

Please see the cloud shadow part in the example provided in requirement 2.5

Snow/Ice Mask

Refers to Section “[Per-Pixel Metadata: Snow/Ice Mask](#)”

Please see the snow part in the example provided in requirement 2.5

Radiometric and Atmospheric Corrections

No examples provided

Geometric Corrections

No examples provided